Linear LED



Project Information				
Project Name:				
Туре:				
Date:				
Location:				
Quantity:				

Description

Kamerton LED Linear Lighting System
The Kamerton is a sleek and versatile LED linear
solution designed for modern architectural spaces.
Available in three standard lengths, it offers flexibility to fit a variety of applications. Choose between
two precise lighting distributions to achieve the
perfect balance of performance and ambiance.
With a palette of 16 body colors, the Kamerton can
blend seamlessly into any design concept or stand
out as a bold statement piece. Ideal for offices,
retail, hospitality, and contemporary interiors, the
Kamerton delivers both style and functionality in
one refined system.projects.



PRODUCT FEATURES

- Pendant mounting
- Single CCT and warmdim
- Direct Indirect Light available.
- Extruded aluminum
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel.
- Polycarbonate satine diffuser is snapped into housing
- Louver anti-glare option available
- Class II/P driver, 0-10V dimming as standard.
- 50,000+ Hours LED Life Expectancy.
- Power factor: >0.9.
- 5 Year Warranty.
- Dry Location
- Ambient Temperature:-30 ~ 40C (22°F to +104°F)





NOTE: Specification subject to change without notice


Linear LED



ORDERING CODE

	SHAPE	LENGTH	DISTRIB	UTION	DIRECT LUMEN	1	INDIRECT LUMEN	LED COLOR
KAM] [
	ST=Straight		D=Dired DI=Dire	ct ct/Indirect	SO=350lm/ft HO=700lm/ft	!	SO=300lm/ft	30K=3000K 40K=4000K WD=Warmdim 2200-3000K 27K=2700K 35K=3500K
	DIMMING	DIRECT OPTIC		INPUT	POWER CABLE	E (CANOPY	BODY COLOR
	D1=0-10V D2=DALI	S=Satine LB=Louver Bla DM= Microprismati		UNV=120-277V 347=347V remote driver	W=White B=Black G=Grey		W=White B=Black C=Specify	See page 3
	MOUNTING	SUSPENSION		DRIVER	COMMENT	S/REQ	UESTS	
	P=Pendant	79=79"		R=Remote				
	POS=Power	C=Specify		Mount				
	Over Suspension	length		*S=Surface Mount				
NOTE: Consult Orbit Illuminations for customizations.			*Surface Mount or max	Jufor EOW		IL YOUR DESIO		

Profile Dimension



^{*}Due to continuing product improvements, Orbit Illuminations reserves the right to change the specifications without notice.

Linear LED



Body colors:

Basic		Standa	ard	Premi	um	
wh	nite (RAL9016)		saphire (RAL 5003)		sandy	night
fo	g (RAL7038)		forrest (RAL 6005)		earth	black dust
gra	aphite (RAL7024)		wine (RAL 3005)		sage	volcano
bla	ack (RAL9005)		ochra		cloudy	marrone

Luminaire Basic Specs





Length	42 inch Length	64 inch Length	86 inch Length
Power	30 W	50 W	70 W
Luminous flux* (direct)	DIRECT up to 2457 lm	DIRECT up to 4095 lm	DIRECT up to 5733 lm
Luminous flux* (indirect)	INDIRECT up to 1227 lm	INDIRECT up to 2045 lm	INDIRECT up to 2863 lm
Optic / Diffuser	satine linear optic, dark microcrystal	satine linear optic, dark microcrystal	satine linear optic, dark microcrystal
Control	ON-OFF, 0-10V, DALI, CASAMBI, DIM TO WARM	ON-OFF, 0-10V, DALI, CASAMBI, DIM TO WARM	ON-OFF, 0-10V, DALI, CASAMBI, DIM TO WARM

LOUVER



Length	42 inch Length	64 inch Length	86 inch Length
Power	29 W	45 W	61 W
Luminous flux* (direct)	up to 2292 lm	up to 3438 lm	up to 4584 lm
Luminous flux* (indirect)	up to 1227 lm	up to 2045 lm	up to 2863 lm
Optic / Diffuser	louver with lens	louver with lens	louver with lens
Control	ON-OFF, 0-10V, DALI, CASAMBI, DIM TO WARM	ON-OFF, 0-10V, DALI, CASAMBI, DIM TO WARM	ON-OFF, 0-10V, DALI, CASAMBI, DIM TO WARM


^{*}Due to continuing product improvements, Orbit Illuminations reserves the right to change the specifications without notice.

Linear LED




POLAR DIAGRAM

DIRECT



DIRECT/INDIRECT




^{*}Due to continuing product improvements, Orbit Illuminations reserves the right to change the specifications without notice.

Linear LED



Power Over Suspension Option - 3mm/0.12" diameter cable suspension (Remote driver)






Example

10 lbs max weight per cable, 20lbs max per linear luminaire.

For Surface LED Driver canopy version (50W max) D5.125" x H1.00"



^{*}Due to continuing product improvements, Orbit Illuminations reserves the right to change the specifications without notice.